



# GIP RUNDO P + BOX



NULAMP



Elegant and slim ceiling lamp, can be used as industrial lighting and modern illumination for your home, office or garage. The LED lamp is equipped with a special, semi-circular light source cover, made of polymethyl methacrylate. It is available with box designed for power supply and wiring, which additionally is designed for an easy mounting of the plafond to the wall surface or the ceiling.

- Lamp: **double anodized aluminium** - grey, can be painted in any colour from the NCS scale.
- Optional transparent blend (glass efficiency 95%), or opal glass (glass transparency 70%): Makrolon®, of Bayer Polymers, **full certification**.
- Highest quality LED **OSRAM DURIS E5** diodes.
- Control: **Dali, 1-10V, KNX, Fibaro**.
- Luminaires design enables **easy maintenance and replacement of light sources**.
- Lamps with a light source were produced in the **European Union**.
- Possibility to **modify a set of lamps for specific customer expectations** (size, colour housing, light colour, type of light source: RGB, RGBW, active white) - [UDESIGN custom](#).

3 Year warranty	Length [cm]	Power [W]	Luminous flux [lm]	Colour temperature [K]	CRI [Ra]
GIPRUNDOOP+BOX 50-11-___	<b>50</b>	11	1050 / 1175 / 1200	3000 / 4000 / 5000	>80
GIPRUNDOOP+BOX 100-22-___	<b>100</b>	22	2100 / 2350 / 2400	3000 / 4000 / 5000	>80
GIPRUNDOOP+BOX 150-33-___	<b>150</b>	33	3150 / 3525 / 3600	3000 / 4000 / 5000	>80
GIPRUNDOOP+BOX 200-44-___	<b>200</b>	44	4200 / 4700 / 4800	3000 / 4000 / 5000	>80
GIPRUNDOOP+BOX 300-66-___	<b>300</b>	66	6300 / 7050 / 7200	3000 / 4000 / 5000	>80
5 Year warranty	Length [cm]	Power [W]	Luminous flux [lm]	Colour temperature [K]	CRI [Ra]
GIPRUNDOOP+BOX 50-6.5-___	<b>50</b>	6,5	620 / 695 / 710	3000 / 4000 / 5000	>80
GIPRUNDOOP+BOX 100-13-___	<b>100</b>	13	1240 / 1390 / 1420	3000 / 4000 / 5000	>80
GIPRUNDOOP+BOX 150-19.5-___	<b>150</b>	19,5	1860 / 2085 / 2130	3000 / 4000 / 5000	>80
GIPRUNDOOP+BOX 200-26-___	<b>200</b>	26	2480 / 2780 / 2840	3000 / 4000 / 5000	>80
GIPRUNDOOP+BOX 300-39-___	<b>300</b>	39	3720 / 4170 / 4260	3000 / 4000 / 5000	>80

LAMP NAME- 100 - 13 - 3000 - M - DALI

1 2 3 4 5

1. Length [cm]	2. Power [W]	3. Colour temperature [K]	4. Cover	5. Control
50, 100, 150, 200, 300 cm special order - 10-300 cm	13 W/m 22 W/m special order - others	3000 K - warm 4000 K - neutral 5000 K - cold special order - 2700K, 6000K	T - transparent M - milk/frosted	Fibaro 1-10 V Dali KNX